

LOCOSYS



Standard Modules

***Sub-meter(L1+L5)
<1m (CEP)***

GNSS Modules		GP	QZSS	GA	GL	BD	Flash	ROM	Position Accuracy	Interface	Application			Dimension(mm)
MTK														
 MC-1010-G									2.5m (CEP)	UART				10.1 x 9.7 x 2.0
MC-1010-B									2.5m (CEP)	UART				10.1 x 9.7 x 2.0
MC-1513-G									1.2m (CEP)	UART/I2C				15.0 x 13.0 x 2.2
MC-1513-B									2.5m (CEP)	UART/I2C				15.0 x 13.0 x 2.2
 MC-1612-G									1.2m (CEP)	UART			 	16.0 x 12.2 x 2.2
MC-1612-B									2.5m (CEP)	UART			 	16.0 x 12.2 x 2.2
MC-1612-G2									1.2m (CEP)	UART			 	16.0 x 12.2 x 2.2
MC-1612-B2									2.5m (CEP)	UART			 	16.0 x 12.2 x 2.2
MC-1722-G									2.5m(CEP)	UART				17.0 x 22.4 x 2.2
MC-1722-B									2.5m(CEP)	UART				17.0 x 22.4 x 2.2
STMicro														
ST-1612i-G									1.8m(CEP)	UART				16.0 x 12.2 x 2.4
ST-1612i-B									1.8m(CEP)	UART				16.0 x 12.2 x 2.4
HED														
HD-1010-GA									2.5m (CEP)	UART				10.1 x 9.7 x 2.2
HD-1010-BA									2.5m (CEP)	UART				10.1 x 9.7 x 2.2
HD-1612-BA									2.5m (CEP)	UART				16.0 x 12.2 x 2.2
※ Application :  HandHeld  Automotive  Drone  Marine  Timing										※  : Hot selling				

Sub-meter Modules		GP	QZSS	GA	GL	BD	IR	Flash	ROM	Position Accuracy	Interface	Application	Dimension(mm)
MTK +1.8V													
 MC-1010-V2a										< 1m (CEP)	UART	   	10.1 x 9.7 x 2.2
 MC-1010-V3a										< 1m (CEP)	UART	   	10.1 x 9.7 x 2.2

Sub-meter Modules		GP	QZSS	GA	GL	BD	IR	Flash	ROM	Position Accuracy	Interface	Application	Dimension(mm)
MTK +3.3V													
 MC-1010-V2b										< 1m (CEP)	UART	   	10.1 x 9.7 x 2.2
 MC-1010-V3b										< 1m (CEP)	UART	   	10.1 x 9.7 x 2.2
 MC-1612-V2b										< 1m (CEP)	UART	  	16.0 x 12.2x 2.4
 MC-1612-V3b										< 1m (CEP)	UART	  	16.0 x 12.2x 2.4

HED +3.3V													
HD-1612-BV1										< 1m (CEP)	UART	  	16.0 x 12.2x 2.4
HD-1612-BV2										< 1m (CEP)	UART	  	16.0 x 12.2x 2.4
HD-1612-BV3										< 1m (CEP)	UART	  	16.0 x 12.2x 2.4

LOCOSYS

Smart Antenna Sub-Meter Antenna



GPS Smart Antenna		GP	QZSS	GA	GL	BD	Flash	ROM	Position Accuracy	Interface	Application			Dimension(mm)
MTK														
	LS2003C								3m (2D RMS)	UART				15.5 x 15.5 x 6.6
	LS2003C-2RE								3m (2D RMS)	UART				15.5 x 15.5 x 6.6
	LS2003D								3m (2D RMS)	UART				21.0 x 17.0 x 7.2
	LS2003D-2RE								3m (2D RMS)	UART				21.0 x 17.0 x 7.2
	LS2003E								1.2m (CEP)	UART				22.0 x 22.0 x 8.4
	LS2003E-2RE								1.2m (CEP)	UART				22.0 x 22.0 x 8.4
	LS2003J-2RE								3m (2D RMS)	UART				16.0 x 12.2 x 2.8
	LS2003H-2RE								3m (CEP)	UART				14.0 x 9.6 x 1.93
	LS20030								3m(2D RMS)	USB				30.0 x 30.0 x 8.0
	LS20031								3m(2D RMS)	TTL				30.0 x 30.0 x 8.0
	LS20032								3m(2D RMS)	RS232				30.0 x 30.0 x 8.0
	LS20030-2RE								3m(2D RMS)	USB				30.0 x 30.0 x 8.0
	LS20031-2RE								3m(2D RMS)	TTL				30.0 x 30.0 x 8.0
	LS20032-2RE								3m(2D RMS)	RS232				30.0 x 30.0 x 8.0
HED														
	LS2008E								2.5m (CEP)	UART				22.0 x 22.0 x 7.5
※ Application :  HandHeld  Automotive  Drone  Marine  Timing														
※  : Hot selling														

GNSS Smart Antenna		GP	QZSS	GA	GL	BD	Flash	ROM	Position Accuracy	Interface	Application	Dimension(mm)
MTK												
	LS2003J-G	●	●	●	●		○		2.5m (CEP)	UART	① ② ④	16.0 x 12.2 x 2.8
	LS2003C-G	●	●	●	●		○		1.2m (CEP)	UART	① ② ④	15.5 x 15.5 x 6.0
	LS2003D-G	●	●	●	●		○		1.2m (CEP)	UART	① ② ④	15.5 x 15.5 x 6.0
	LS2003E-G	●	●	●	●		○		1.2m (CEP)	UART	① ② ④	22.0 x 22.0 x 8.4
	LS2003G-G-T	●	●	●	●		○		2.5 m (CEP)	TTL	① ② ③ ④	30.0 x 30.0 x 8.0
	LS2003G-G-R	●	●	●	●		○		2.5 m (CEP)	RS232	① ② ③ ④	30.0 x 30.0 x 8.0
	LS2003G-G2-T	●	●	●	●		○		2.5 m (CEP)	TTL	① ② ③ ④ ⑤	30.0 x 30.0 x 8.0
	LS2003G-G2-R	●	●	●	●		○		2.5 m (CEP)	RS232	① ② ③ ④ ⑤	30.0 x 30.0 x 8.0
	LS2003G-B2-T	●	●	●		●	○		2.5 m (CEP)	TTL	① ② ③ ④ ⑤	30.0 x 30.0 x 8.0
	LS2003G-B2-R	●	●	●		●	○		2.5 m (CEP)	RS232	① ② ③ ④ ⑤	30.0 x 30.0 x 8.0
	LS20030-G	●	●	●	●		○		2.5m (CEP)	USB	① ② ③ ④	30.0 x 30.0 x 8.0
	LS20031-G	●	●	●	●		○		2.5m (CEP)	TTL	① ② ③ ④	30.0 x 30.0 x 8.0
	LS20032-G	●	●	●	●		○		2.5m (CEP)	RS232	① ② ③ ④	30.0 x 30.0 x 8.0

GNSS Smart Antenna	GP	QZSS	GA	GL	BD	Flash	ROM	Position Accuracy	Interface	Application	Dimension(mm)
MTK											
LS20030-B	●	●	●		●	○		2.5m (CEP)	USB	① ② ③ ④	30.0 x 30.0 x 8.0
LS20031-B	●	●	●		●	○		2.5m (CEP)	TTL	① ② ③ ④	30.0 x 30.0 x 8.0
LS20032-B	●	●	●		●	○		2.5m (CEP)	RS232	① ② ③ ④	30.0 x 30.0 x 8.0
LS20030U-G	●	●	●	●		○		2.5m (CEP)	USB	① ② ③ ④ ⑤	30.0 x 30.0 x 8.0
LS20031U-G	●	●	●	●		○		2.5m (CEP)	TTL	① ② ③ ④ ⑤	30.0 x 30.0 x 8.0
LS20032U-G	●	●	●	●		○		2.5m (CEP)	RS232	① ② ③ ④ ⑤	30.0 x 30.0 x 8.0
LS20030U-B	●	●	●		●	○		2.5m (CEP)	USB	① ② ③ ④ ⑤	30.0 x 30.0 x 8.0
LS20031U-B	●	●	●		●	○		2.5m (CEP)	TTL	① ② ③ ④ ⑤	30.0 x 30.0 x 8.0
LS20032U-B	●	●	●		●	○		2.5m (CEP)	RS232	① ② ③ ④ ⑤	30.0 x 30.0 x 8.0
HED											
LS2008E-G	●	●	●	●	●	○		< 2.5m (CEP)	UART	① ② ④	22.0 x 22.0 x 7.5
STMicro											
LS2009G-G-T	●	●	●	●		○		< 1.6m (CEP)	TTL	① ② ③ ④	30.0 x 30.0 x 8.0
LS2009G-G-R	●	●	●	●		○		< 1.6m (CEP)	RS232	① ② ③ ④	30.0 x 30.0 x 8.0

LOCOSYS



GNSS Mouse
Sub-Meter Mouse

GPS Mouse		GP	QZSS	GA	GL	BD	Position Accuracy	Interface	Connector	Application	Dimension(mm)
MTK											
 LS23030							2.5m	USB	USB	  	49.0 x 41.0 x 14.1
LS23032							2.5m	RS232	PS2	  	49.0 x 41.0 x 14.1
LS23033							2.5m	RS232	RJ11	  	49.0 x 41.0 x 14.1
 LS23035							2.5m	RS232	PS2	  	49.0 x 41.0 x 14.1
 LS23036							2.5m	RS232	RJ11	  	49.0 x 41.0 x 14.1
LS23030-2RE							2.5m	USB	USB	  	49.0 x 41.0 x 14.1
LS23032-2RE							2.5m	RS232	PS2	  	49.0 x 41.0 x 14.1
LS23033-2RE							2.5m	RS232	RJ11	  	49.0 x 41.0 x 14.1
LS23035-2RE							2.5m	RS232	PS21	  	49.0 x 41.0 x 14.1
LS23036-2RE							2.5m	RS232	RJ11	  	49.0 x 41.0 x 14.1

GNSS Mouse		GP	QZSS	GA	GL	BD	Position Accuracy	Interface	Connector	Application		Dimension(mm)	
MTK													
	LS23030-G						2.5m	USB	USB			49.0 x 41.0 x 14.1	
	LS23032-G						2.5m	RS232	PS2			49.0 x 41.0 x 14.1	
	LS23033-G						2.5m	RS232	RJ11			49.0 x 41.0 x 14.1	
	LS23035-G						2.5m	RS232	PS2			49.0 x 41.0 x 14.1	
	LS23036-G						2.5m	RS232	RJ11			49.0 x 41.0 x 14.1	
STMicro													
	LS23092-G						1.6m	RS232	PS2				49.0 x 41.0 x 14.1
	LS23093-G						1.6m	RS232	RJ11				49.0 x 41.0 x 14.1
	LS23095-G						1.6m	RS232	PS2				49.0 x 41.0 x 14.1
	LS23096-G						1.6m	RS232	RJ11				49.0 x 41.0 x 14.1
	LS23092-G2						1.6m	RS232	PS2				49.0 x 41.0 x 14.1
	LS23093-G2						1.6m	RS232	RJ11				49.0 x 41.0 x 14.1
	LS23095-G2						1.6m	RS232	PS2				49.0 x 41.0 x 14.1
	LS23096-G2						1.6m	RS232	RJ11				49.0 x 41.0 x 14.1

Dead Reckoning Mouse	GP	QZSS	GA	GL	BD	Position Accuracy	Interface	Connector	Application	Dimension(mm)
----------------------	----	------	----	----	----	-------------------	-----------	-----------	-------------	---------------

MTK

LS23030-UDG						2.5m	USB	USB	2 3	49.0 x 41.0 x 14.1
LS23032-UDG						2.5m	RS232	PS2	2 3	49.0 x 41.0 x 14.1
LS23035-UDG						2.5m	RS232	PS2	2 3	49.0 x 41.0 x 14.1
LS23036-UDG						2.5m	RS232	RJ11	2 3	49.0 x 41.0 x 14.1

Sub-meter Mouse		GP	QZSS	GA	GL	BD	IR	Position Accuracy	Interface	Connector	Application		Dimension(mm)
MTK													
	LS23030-V2							< 1m	USB	USB	 	 	49.0 x 41.0 x 14.1
	LS23032-V2							< 1m	RS232	PS2	 	 	49.0 x 41.0 x 14.1
	LS23033-V2							< 1m	RS232	RJ11	 	 	49.0 x 41.0 x 14.1
	LS23035-V2							< 1m	RS232	PS2	 	 	49.0 x 41.0 x 14.1
	LS23036-V2							< 1m	RS232	RJ11	 	 	49.0 x 41.0 x 14.1
	LS23030-V3							< 1m	USB	USB	 	 	49.0 x 41.0 x 14.1
	LS23032-V3							< 1m	RS232	PS2	 	 	49.0 x 41.0 x 14.1
	LS23033-V3							< 1m	RS232	RJ11	 	 	49.0 x 41.0 x 14.1
	LS23035-V3							< 1m	RS232	PS2	 	 	49.0 x 41.0 x 14.1
	LS23036-V3							< 1m	RS232	RJ11	 	 	49.0 x 41.0 x 14.1

Sub-meter Mouse	GP	QZSS	GA	GL	BD	IR	Position Accuracy	Interface	Connector	Application	Dimension(mm)
HED											
LS23080-BV2							< 1m	USB	USB	   	49.0 x 41.0 x 14.1
LS23082-BV2							< 1m	RS232	PS2	   	49.0 x 41.0 x 14.1
LS23083-BV2							< 1m	RS232	RJ11	   	49.0 x 41.0 x 14.1
LS23085-BV2							< 1m	RS232	PS2	   	49.0 x 41.0 x 14.1
LS23086-BV2							< 1m	RS232	RJ11	   	49.0 x 41.0 x 14.1
LS23080-BV3							< 1m	USB	USB	   	49.0 x 41.0 x 14.1
LS23082-BV3							< 1m	RS232	PS2	   	49.0 x 41.0 x 14.1
LS23083-BV3							< 1m	RS232	RJ11	   	49.0 x 41.0 x 14.1
LS23085-BV3							< 1m	RS232	PS2	   	49.0 x 41.0 x 14.1
LS23086-BV3							< 1m	RS232	RJ11	   	49.0 x 41.0 x 14.1

LOCOSYS

Dead Reckoning Technology



Dead Reckoning Modules		GP	QZSS	GA	GL	BD	Flash	ROM	Position Accuracy	Dead Reckoning	P/R/Y	Interface	Application	Dimension(mm)
MTK														
	MC-1612-DG (ADR/UDR)								2.5m (CEP) 0.5% (ADR) 5% (UDR)			UART	  	16.0 x 12.2 x 2.4
	MC-1612-DB (ADR/UDR)								2.5m (CEP) 0.5% (ADR) 5% (UDR)			UART	  	16.0 x 12.2 x 2.4
STMicro														
	ST-1612i-DGO (ADR)								1.8m (CEP) 0.5% (ADR)			ODO		16.0 x 12.2 x 2.3
	ST-1612i-DGU (UDR)								1.8m (CEP) 5% (UDR)			UART		16.0 x 12.2 x 2.3
	ST-1612i-DBO (ADR)								1.8m (CEP) 0.5% (ADR)			ODO		16.0 x 12.2 x 2.3
	ST-1612i-DBU (UDR)								1.8m (CEP) 5% (UDR)			UART		16.0 x 12.2 x 2.3
	ST-1612r-DGO (ADR)								1.8m (CEP) 0.5% (ADR)			ODO		16.0 x 12.2 x 2.3
	ST-1612r-DGU (UDR)								1.8m (CEP) 5% (UDR)			UART		16.0 x 12.2 x 2.3
	ST-1612r-DBO (ADR)								1.8m (CEP) 0.5% (ADR)			ODO		16.0 x 12.2 x 2.3
	ST-1612r-DBU (UDR)								1.8m (CEP) 5% (ADR)			UART		16.0 x 12.2 x 2.3
※ ADR /UDR : Automotive Dead Reckoning/ Untethered Dead Reckoning										※ P/ R/ Y : Pitch/ Roll/ Yaw				
※ Application :  HandHeld  Automotive  Drone  Marine  Timing										※ ODO : Odometer signal input				
										※  : Hot selling				

Dead Reckoning Modules	GP	QZSS	GA	GL	BD	Flash	ROM	Position Accuracy	Dead Reckoning	P/ R/ Y	Interface	Application	Dimension(mm)
------------------------	----	------	----	----	----	-------	-----	-------------------	----------------	---------	-----------	-------------	---------------

STMicro

(All electrical parts pass AEC-Q100)

ST-1612A-DGO (ADR)								1.8m (CEP) 0.5% (ADR)			ODO	2	16.0 x 12.2 x 2.4
ST-1612A-DGU (UDR)								1.8m (CEP) 5% (UDR)			UART	2	16.0 x 12.2 x 2.4
ST-1612A-DBO (ADR)								1.8m (CEP) 0.5% (ADR)			ODO	2	16.0 x 12.2 x 2.4
ST-1612A-DBU (UDR)								1.8m (CEP) 5% (UDR)			UART	2	16.0 x 12.2 x 2.4

DR End Products	GP	QZSS	GA	GL	BD	Flash	ROM	Position Accuracy	Dead Reckoning	P/ R/ Y	Interface	Application	Dimension(mm)
-----------------	----	------	----	----	----	-------	-----	-------------------	----------------	---------	-----------	-------------	---------------

MTK

G310 (ADR)								1.8m (CEP)			BT	1 2	96.0 x 63.0 x 14.7
B310 (ADR)								1.8m (CEP)			BT	1 2	96.0 x 63.0 x 14.7
 G310-U (UDR)								2.5m (CEP)			BT	1 2	96.0 x 63.0 x 14.7
B310-U (UDR)								2.5m (CEP)			BT	1 2	96.0 x 63.0 x 14.7

※ ADR /UDR : Automotive Dead Reckoning/ Untethered Dead Reckoning

※ Application : ① HandHeld ② Automotive ③ Drone ④ Marine ⑤ Timing

※ P/ R/ Y : Pitch/ Roll/ Yaw

※ ODO : Odometer signal input

※



 : Hot selling

LOCOSYS



Base station

Rover

Rover

Rover

Rover

Rover

RTK Solution

RTK Modules		GP	QZSS	GA	GL	BD	IR	Position Accuracy	Heading Accuracy	Dead Reckoning	P/R/Y	Interface	Application	Dimension(mm)
	RTK-1010							0.01m+1ppm	< 0.2deg			UART	  	10.1 x 9.7 x 2.2

RTK Embedded board		GP	QZSS	GA	GL	BD	IR	Position Accuracy	Heading Accuracy	Dead Reckoning	P/R/Y	Interface	Application	Dimension(mm)
	RTK-4671-MH							0.01m+1ppm				UART	  	71.0 x 46.0 x 7.7
	RTK-4671-MHDR							0.01m+1ppm				UART	  	71.0 x 46.0 x 7.7
	RTK-4671-MHPD							0.01m+1ppm	< 0.2deg			UART	  	71.0 x 46.0 x 7.7

RTK USB Dongle		GP	QZSS	GA	GL	BD	IR	Position Accuracy	Heading Accuracy	Dead Reckoning	P/R/Y	Interface	Application	Dimension(mm)
	RTK-4P							0.01m+1ppm				Type C		27.5(D) x 95.0(H)

RTK Box (4G-LTE)		GP	QZSS	GA	GL	BD	IR	Position Accuracy	Heading Accuracy	Dead Reckoning	P/R/Y	Interface	Application	Dimension(mm)
	RTK-M100							0.01m+1ppm					 	98.0 x 82.0 x 40.0
	RTK-M200							0.01m+1ppm					 	98.0 x 82.0 x 40.0

※ P/ R/ Y : Pitch/ Roll/ Yaw

※ Application : HandHeld Automotive Drone Marine Timing

※  : Hot selling

LOCOSYS

Timing Module



PCIe Card



PCle Card	GP	QZSS	GA	GL	BD	Flash	ROM	Position Accuracy	Interface	Application	Dimension(mm)
MTK											
LS26030	●	●				○		3m (2D RMS)	USB	① ②	50.8 x 28.5 x 3.2
LS26030-2RE	●	●					○	3m (2D RMS)	USB	① ②	50.8 x 28.5 x 3.2
LS26030-B	●	●	●		●	○		2.5m (CEP)	USB	① ②	50.8 x 28.5 x 3.2
LS26030-G	●	●	●	●		○		2.5m (CEP)	USB	① ②	50.8 x 28.5 x 3.2

Mini PCle Card	GP	QZSS	GA	GL	BD	Flash	ROM	Position Accuracy	Interface	Application	Dimension(mm)
MTK											
LS26031	●	●				○		3m (2D RMS)	USB	① ②	26.65 x 28.5 x 3.2
LS26031-2RE	●	●					○	3m (2D RMS)	USB	① ②	26.65 x 28.5 x 3.2
LS26031-B	●	●	●		●	○		2.5m (CEP)	USB	① ②	26.65 x 28.5 x 3.2
LS26031-G	●	●	●	●		○		2.5m (CEP)	USB	① ②	26.65 x 28.5 x 3.2

Timing module	GP	QZSS	GA	GL	BD	Flash	ROM	Position Accuracy	Interface	Application	Dimension(mm)
STMicro											
ST-1612-T	●			●		○		2.5m (CEP)	UART/I2C USB/CAN Bus	⑤	16.0 x 12.2 x 2.2
 ST-1612i-GT	●	●	●	●		○		1.8m (CEP)	UART	⑤	16.0 x 12.2 x 2.4
 ST-1612i-GTs	●	●	●	●		○		1.8m (CEP)	USB	⑤	16.0 x 12.2 x 2.4
ST-1612i-BT	●	●	●		●	○		1.8m (CEP)	UART	⑤	16.0 x 12.2 x 2.4
ST-1612i-BTs	●	●	●		●	○		1.8m (CEP)	USB	⑤	16.0 x 12.2 x 2.4

Timing PCIe Card	GP	QZSS	GA	GL	BD	Flash	ROM	Position Accuracy	Interface	Application	Dimension(mm)
STMicro											
LS26090-GT	●	●	●	●		○		1.8m (CEP)	USB	⑤	50.8 x 28.5 x 3.5

Timing Mini PCIe Card	GP	QZSS	GA	GL	BD	Flash	ROM	Position Accuracy	Interface	Application	Dimension(mm)
STMicro											
LS26091-GT	●	●	●	●		○		1.8m (CEP)	USB	⑤	26.65 x 28.5 x 3.5

※ Application : ① HandHeld ② Automotive ③ Drone ④ Marine ⑤ Timing

※  : Hot selling

LOCOSYS

20F.-13, No.79, Sec. 1, Xintai 5th Rd.
Xizhi Dist., New Taipei City 22101
Taiwan R.O.C.
www.locosystech.com

Tel : 886-2-8698-3698
Fax : 886-2-8698-3699
Mail : info@locosystech.com

